

PT-H3500

Polyurethane Paint Sprayer

Two-component Ultra High Pressure
Polyurethane Paint Sprayer.

Feature

- ⌚ High Performance Spraying System
- ⌚ Powerful and Stable Driving Force
- ⌚ Rapid Heating
- ⌚ Excellent Atomization Effect
- ⌚ Convenient to Move
- ⌚ Demanding Design



Specification

Model:	PT-H3500
Ratio of Raw Material:	1:1
Raw Material Viscosity Range:	200-1000CPS
Heater Heating Power:	9000W×2
Pipe Insulation Heating Power Tube:	3200W
Power Requirements:	Three-phase four wire 380V, 50Hz
Working Fluid Pressure:	8-12Mpa
Single-Component Raw Material Output Pressure:	26Mpa
System Pressure:	25Mpa
Gross weight:	250KGS
Package:	110*100*135CM

Application Scope

Spraying projects, anti-corrosive projects, fireproofing projects and waterproofing projects in large residential, commercial and industrial construction.

Coatings and Paints

Polyurea elastomer, polyurethane elastomer, foamed polyurethane material, pu adhesive, sealant.

Standard Configuration

- 15m Heat Preservation Hose × 1
- 3M Whip Hose × 2
- Supply Pump × 2
- Spray Gun × 1
- Lubricating Oil × 1
- Tool Kit × 1

