

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.05.2024

Version number 78 (replaces version 77)

Revision: 24.05.2024

* **SECTION 1: Identification of the substance/mixture and of the company/undertaking**

- **1.1 Product identifier**

- **Trade name:** POLURAN 191 INTRADUR 10

- **Article number:** 191

- **UFI:** YMJ1-70XU-U00K-3X1K

- **1.2 Relevant identified uses of the substance or mixture and uses advised against**

- **Sector of Use**

- SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

- **Product category** PC9a Coatings and paints, thinners, paint removers

- **Process category**

- PROC10 Roller application or brushing

- PROC7 Industrial spraying

- **Technical function** Dye

- **Application of the substance / the mixture** Paint

- **1.3 Details of the supplier of the safety data sheet**

- **Manufacturer/Supplier:**

- Baril Coatings BV

- Zilverenberg 9

- 5234 GL 's-Hertogenbosch

- Tel +31 (0)73 6419890

- e-mail info@baril.nl

- The Netherlands

- **Further information obtainable from:**

- Product Safety Department

- R&D department

- **1.4 Emergency telephone number:** 800-424-9300

* **SECTION 2: Hazards identification**

- **2.1 Classification of the substance or mixture**

- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- **2.2 Label elements**

- **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

EU

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.05.2024

Version number 78 (replaces version 77)

Revision: 24.05.2024

Trade name: POLURAN 191 INTRADUR 10

(Contd. of page 1)

· Hazard pictograms


GHS02 GHS07

· Signal word Warning

· Hazard-determining components of labelling:

Acrylic copolymer (1.7.04)

Vetzuren, tall-olie,
verbindingen met oleylamine
· Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P241 Use explosion-proof [electrical/ventilating/lighting] equipment.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Additional information:

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

· 2.3 Other hazards
· Results of PBT and vPvB assessment

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

Description: Resin mixture

· Dangerous components:

| | | |
|---|-------------------------------------|---------|
| CAS: 1330-20-7 EINECS: 215-535-7 Index number: 601-022-00-9 | xylene | 10-<15% |
| | Acrylic copolymer (1.7.04) | 10-<15% |
| CAS: 108-65-6 EINECS: 203-603-9 Index number: 607-195-00-7 Reg.nr.: 01-2119475791-29 | 2-methoxy-1-methylethyl acetate | 5-<7% |

(Contd. on page 3)

EU

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.05.2024

Version number 78 (replaces version 77)

Revision: 24.05.2024

Trade name: POLURAN 191 INTRADUR 10

| (Contd. of page 2) | | |
|---|--|-----------|
| CAS: 64742-95-6 EC number: 918-668-5 Reg.nr.: 01-2119455851-35 | Solvent naphtha (petroleum), light arom.  Flam. Liq. 3, H226;  Asp. Tox. 1, H304;  Aquatic Chronic 2, H411;  STOT SE 3, H335-H336, EUH066 | 3-<5% |
| CAS: 100-41-4 EINECS: 202-849-4 Index number: 601-023-00-4 Reg.nr.: 01-2119489370-35 | ethylbenzene  Flam. Liq. 2, H225;  STOT RE 2, H373; Asp. Tox. 1, H304;  Acute Tox. 4, H332; Aquatic Chronic 3, H412 | 3-<5% |
| CAS: 123-86-4 EINECS: 204-658-1 Index number: 607-025-00-1 Reg.nr.: 01-2119485493-29 | n-butyl acetate  Flam. Liq. 3, H226;  STOT SE 3, H336, EUH066 | 1-<2.5% |
| CAS: 85711-55-3 EINECS: 288-315-1 Reg.nr.: 01-2119974148-28 | Vetzuren, tallolie, verbindingen met oleylamine  STOT RE 2, H373;  Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1A, H317 | 0.1-0.15% |

• **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:**
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture**
No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**
Do not allow product to reach sewage system or any water course.

(Contd. on page 4)

EU

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.05.2024

Version number 78 (replaces version 77)

Revision: 24.05.2024

Trade name: POLURAN 191 INTRADUR 10

(Contd. of page 3)

Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.

• 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.

• 6.4 Reference to other sections

See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

• 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.
No special measures required.

• Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.

• 7.2 Conditions for safe storage, including any incompatibilities

• Storage:

• Requirements to be met by storerooms and receptacles: No special requirements.

• Information about storage in one common storage facility: Not required.

• Further information about storage conditions: Keep container tightly sealed.

• 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

• 8.1 Control parameters

• Ingredients with limit values that require monitoring at the workplace:

CAS: 1330-20-7 xylene

| | |
|-------|--|
| IOELV | Short-term value: 442 mg/m ³ , 100 ppm Long-term value: 221 mg/m ³ , 50 ppm Skin |
|-------|--|

CAS: 108-65-6 2-methoxy-1-methylethyl acetate

| | |
|-------|--|
| IOELV | Short-term value: 550 mg/m ³ , 100 ppm Long-term value: 275 mg/m ³ , 50 ppm Skin |
|-------|--|

CAS: 100-41-4 ethylbenzene

| | |
|-------|---|
| IOELV | Short-term value: 884 mg/m ³ , 200 ppm Long-term value: 442 mg/m ³ , 100 ppm Skin |
|-------|---|

CAS: 123-86-4 n-butyl acetate

| | |
|-------|--|
| IOELV | Short-term value: 723 mg/m ³ , 150 ppm Long-term value: 241 mg/m ³ , 50 ppm |
|-------|--|

• Additional information: The lists valid during the making were used as basis.

• 8.2 Exposure controls

• Appropriate engineering controls No further data; see item 7.

(Contd. on page 5)

EU

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.05.2024

Version number 78 (replaces version 77)

Revision: 24.05.2024

Trade name: POLURAN 191 INTRADUR 10

(Contd. of page 4)

· Individual protection measures, such as personal protective equipment

· General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Hand protection



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection



Tightly sealed goggles

* SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Physical state

Fluid

· Colour:

According to product specification

· Odour:

Characteristic

· Odour threshold:

Not determined.

· Melting point/freezing point:

Undetermined.

**· Boiling point or initial boiling point and
boiling range**

137-143 °C (CAS: 1330-20-7 xylene)

· Flammability

Flammable.

· Lower and upper explosion limit

1.1 Vol % (CAS: 1330-20-7 xylene)

· Lower:

7 Vol % (CAS: 1330-20-7 xylene)

· Upper:

(Contd. on page 6)

EU

**Safety data sheet
according to 1907/2006/EC, Article 31**

Printing date 24.05.2024

Version number 78 (replaces version 77)

Revision: 24.05.2024

Trade name: POLURAN 191 INTRADUR 10

| | | |
|--|---|--------------------|
| | | (Contd. of page 5) |
| · Flash point: | 30 °C | |
| · Ignition temperature: | 315 °C (CAS: 108-65-6 2-methoxy-1-methylethyl acetate) | |
| · Decomposition temperature: | Not determined. | |
| · pH | Mixture is non-polar/aprotic. | |
| · Viscosity: | | |
| · Kinematic viscosity at 20 °C | >60 s (ISO 6 mm) | |
| · Dynamic: | Not determined. | |
| · Solubility | | |
| · water: | Not miscible or difficult to mix. | |
| · Partition coefficient n-octanol/water (log value) | Not determined. | |
| · Vapour pressure at 20 °C: | 6.7-8.2 hPa (CAS: 1330-20-7 xylene) | |
| · Density and/or relative density | | |
| · Density at 20 °C: | 1.512 g/cm ³ | |
| · Relative density | Not determined. | |
| · Vapour density | Not determined. | |
| · 9.2 Other information | | |
| · Appearance: | | |
| · Form: | Fluid | |
| · Important information on protection of health and environment, and on safety. | | |
| · Auto-ignition temperature: | Product is not selfigniting. | |
| · Explosive properties: | Product is not explosive. However, formation of explosive air/vapour mixtures are possible. | |
| · Solvent content: | | |
| · Organic solvents: | 30.2 % | |
| · VOC (EC) | 29.67 % | |
| · Solids content: | 70.2 % | |
| · Change in condition | | |
| · Evaporation rate | Not determined. | |
| · Information with regard to physical hazard classes | | |
| · Explosives | Void | |
| · Flammable gases | Void | |
| · Aerosols | Void | |
| · Oxidising gases | Void | |
| · Gases under pressure | Void | |
| · Flammable liquids | Flammable liquid and vapour. | |
| · Flammable solids | Void | |
| · Self-reactive substances and mixtures | Void | |
| · Pyrophoric liquids | Void | |
| · Pyrophoric solids | Void | |
| · Self-heating substances and mixtures | Void | |
| · Substances and mixtures, which emit flammable gases in contact with water | Void | |
| · Oxidising liquids | Void | |
| · Oxidising solids | Void | |
| · Organic peroxides | Void | |
| · Corrosive to metals | Void | |

(Contd. on page 7)

EU

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.05.2024

Version number 78 (replaces version 77)

Revision: 24.05.2024

Trade name: POLURAN 191 INTRADUR 10

- Desensitised explosives

Void

(Contd. of page 6)

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

- **LD/LC50 values relevant for classification:**

CAS: 1330-20-7 xylene

| | | |
|------------|----------|----------------------|
| Oral | LD50 | 4,300 mg/kg (rat) |
| Dermal | LD50 | 2,000 mg/kg (rabbit) |
| Inhalative | LC50/4 h | 27.12 mg/l (rat) |

- **Skin corrosion/irritation** Causes skin irritation.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

Additional toxicological information:

- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**

Based on available data, the classification criteria are not met.

11.2 Information on other hazards

- **Endocrine disrupting properties**

CAS: 68512-30-1 Phenol, methylstyrenated

List II

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

(Contd. on page 8)

EU

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.05.2024

Version number 78 (replaces version 77)

Revision: 24.05.2024

Trade name: POLURAN 191 INTRADUR 10

(Contd. of page 7)

- **12.6 Endocrine disrupting properties**

For information on endocrine disrupting properties see section 11.

- **12.7 Other adverse effects**

- **Remark:** Harmful to fish

- **Additional ecological information:**

- **General notes:**

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**

- **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- **Uncleaned packaging:**

- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- **14.1 UN number or ID number**

Void

· **ADR/RID/ADN, ADN, IMDG** UN1263

- **IATA**

- **14.2 UN proper shipping name**

Void

· **ADR/RID/ADN, ADN, IMDG**

PAINT

- **IATA**

- **14.3 Transport hazard class(es)**

- **ADR/RID/ADN, IMDG**

Void

- **Class**

- **ADN**

Void

- **ADN/R Class:**

-

- **IATA**



- **Class**

3 Flammable liquids.

- **Label**

3

- **14.4 Packing group**

Void

· **ADR/RID/ADN, IMDG**

III

- **IATA**

III

- **14.5 Environmental hazards:**

Not applicable.

- **14.6 Special precautions for user**

Not applicable.

- **14.7 Maritime transport in bulk according to IMO instruments**

Not applicable.

(Contd. on page 9)

EU

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.05.2024

Version number 78 (replaces version 77)

Revision: 24.05.2024

Trade name: POLURAN 191 INTRADUR 10

(Contd. of page 8)

· Transport/Additional information:
· ADR/RID/ADN
· Remarks:

> 450 l: 3 F1, III

· IMDG
· Remarks:

> 450 l: 3, III

· UN "Model Regulation":

Void

SECTION 15: Regulatory information
· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms


GHS02 GHS07

· Signal word Warning

· Hazard-determining components of labelling:

Acrylic copolymer (1.7.04)

Vetzuren, tall-olie,

verbindingen met oleylamine

· Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P241 Use explosion-proof [electrical/ventilating/lighting] equipment.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Directive 2012/18/EU
· Named dangerous substances - ANNEX I None of the ingredients is listed.

· Seveso category P5c FLAMMABLE LIQUIDS
· Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t

· Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

· REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

(Contd. on page 10)

EU

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.05.2024

Version number 78 (replaces version 77)

Revision: 24.05.2024

Trade name: POLURAN 191 INTRADUR 10

(Contd. of page 9)

· **DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**

None of the ingredients is listed.

· **REGULATION (EU) 2019/1148**

· **Regulation (EC) No 273/2004 on drug precursors**

None of the ingredients is listed.

· **Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors**

None of the ingredients is listed.

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

This safety data sheet is in compliance with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

· **Relevant phrases**

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

· **Department issuing SDS:** product safety department

· **Contact:**

· **Date of previous version:** 08.11.2023

· **Version number of previous version:** 77

· **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

(Contd. on page 11)

-EU

**Safety data sheet
according to 1907/2006/EC, Article 31**

Printing date 24.05.2024

Version number 78 (replaces version 77)

Revision: 24.05.2024

Trade name: POLURAN 191 INTRADUR 10

(Contd. of page 10)

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Skin Sens. 1A: Skin sensitisation – Category 1A

Skin Sens. 1B: Skin sensitisation – Category 1B

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

* Data compared to the previous version altered.

EU