

*** SECTION 1: Identification of the substance/mixture and of the company/undertaking****· 1.1 Product identifier****· Trade name: STEELKOTE EP AC+****· Article number: 803****· UFI: KC74-50AJ-300P-S0SS****· 1.2 Relevant identified uses of the substance or mixture and uses advised against****· Sector of Use**

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

· Product category PC9a Coatings and paints, thinners, paint removers**· Process category**

PROC7 Industrial spraying

PROC10 Roller application or brushing

· Technical function Dye**· Application of the substance / the mixture** Paint**· 1.3 Details of the supplier of the safety data sheet****· Manufacturer/Supplier:**

Baril Coatings BV

Zilverenberg 9

5234 GL 's-Hertogenbosch

Tel +31 (0)73 6419890

e-mail info@baril.nl

The Netherlands

· Further information obtainable from:

Product Safety Department

R&D department

· 1.4 Emergency telephone number:

General emergency number: 112

Belgium: +32 (0) 70 245 245

France: + 33 (0)1 45 42 59 59

Germany: +49-30-18412-0

Great britain: 111

The Netherlands: +31 (0)88 755 8000

Poland: +48 42 2538 400

Romania: +40215992300

Slovakia: 0421 (0) 2 5477 4166

Serbia: +7 343 229 98 57

Use this emergency number for immediate help in case of poisoning.

*** SECTION 2: Hazards identification****· 2.1 Classification of the substance or mixture****· Classification according to Regulation (EC) No 1272/2008**

GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.

(Contd. on page 2)

EU

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 03.07.2024

Version number 54 (replaces version 53)

Revision: 03.07.2024

Trade name: STEELKOTE EP AC+

(Contd. of page 1)



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

2.2 Label elements**Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

Hazard pictograms

GHS02



GHS07

Signal word Warning**Hazard-determining components of labelling:**

phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2,2'-(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bis[oxirane]
 Phenol, methylstyrenated
 bis-[4-(2,3-epoxypropoxy)fenyl]propaan
 oxirane, mono[(C12-14-alkyloxy)methyl] derivs

Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P241 Use explosion-proof [electrical/ventilating/lighting] equipment.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

2.3 Other hazards**Results of PBT and vPvB assessment**

PBT: Not applicable.

vPvB: Not applicable.

(Contd. on page 3)

EU

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 03.07.2024

Version number 54 (replaces version 53)

Revision: 03.07.2024

Trade name: STEELKOTE EP AC+

(Contd. of page 2)

• Determination of endocrine-disrupting properties

CAS: 68512-30-1 Phenol, methylstyrenated

List II

SECTION 3: Composition/information on ingredients
• 3.2 Mixtures
Description: Resin mixture

• Dangerous components:

CAS: 14808-60-7 EINECS: 238-878-4	Quartz (SiO ₂) substance with a Community workplace exposure limit	10-<15%
CAS: 25036-25-3 EC number: 682-390-8	phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bis[oxirane] ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	10-<15%
CAS: 1330-20-7 EINECS: 215-535-7 Index number: 601-022-00-9	xylene ⚠ Flam. Liq. 3, H226; ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	7-<10%
CAS: 68512-30-1 EINECS: 270-966-8	Phenol, methylstyrenated ⚠ Skin Sens. 1, H317; Aquatic Chronic 3, H412	5-<7%
CAS: 108-65-6 EINECS: 203-603-9 Index number: 607-195-00-7 Reg.nr.: 01-2119475791-29	2-methoxy-1-methylethyl acetate ⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336	3-<5%
CAS: 100-41-4 EINECS: 202-849-4 Index number: 601-023-00-4 Reg.nr.: 01-2119489370-35	ethylbenzene ⚠ Flam. Liq. 2, H225; ⚠ STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H332; Aquatic Chronic 3, H412	1-<2.5%
CAS: 14808-60-7 EINECS: 238-878-4	Quartz (SiO ₂) ⚠ Acute Tox. 4, H332	1-<2.5%
	bis-[4-(2,3-epoxypropoxy)fenyl]propan ⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317 Specific concentration limits: Eye Irrit. 2; H319: C ≥ 5 % Skin Irrit. 2; H315: C ≥ 5 %	1-<2.5%
CAS: 68609-97-2 EINECS: 271-846-8 Index number: 603-103-00-4 Reg.nr.: 01-2119485289-22	oxirane, mono[(C ₁₂ -14-alkyloxy)methyl] derivs ⚠ Skin Irrit. 2, H315; Skin Sens. 1, H317	1-<2.5%

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures
• 4.1 Description of first aid measures
General information: Immediately remove any clothing soiled by the product.

• After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

(Contd. on page 4)

EU

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 03.07.2024

Version number 54 (replaces version 53)

Revision: 03.07.2024

Trade name: STEELKOTE EP AC+

(Contd. of page 3)

- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

* **SECTION 5: Firefighting measures**

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture**
No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.

* **SECTION 6: Accidental release measures**

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

* **SECTION 7: Handling and storage**

- **7.1 Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
No special measures required.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.
- **7.3 Specific end use(s)** No further relevant information available.

- EU -

(Contd. on page 5)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 03.07.2024

Version number 54 (replaces version 53)

Revision: 03.07.2024

Trade name: STEELKOTE EP AC+

(Contd. of page 4)

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

CAS: 14808-60-7 Quartz (SiO₂)

BOELV	Long-term value: 0.1* mg/m ³ *respirable fraction
-------	---

CAS: 1330-20-7 xylene

IOELV	Short-term value: 442 mg/m ³ , 100 ppm Long-term value: 221 mg/m ³ , 50 ppm Skin
-------	--

CAS: 108-65-6 2-methoxy-1-methylethyl acetate

IOELV	Short-term value: 550 mg/m ³ , 100 ppm Long-term value: 275 mg/m ³ , 50 ppm Skin
-------	--

CAS: 100-41-4 ethylbenzene

IOELV	Short-term value: 884 mg/m ³ , 200 ppm Long-term value: 442 mg/m ³ , 100 ppm Skin
-------	---

CAS: 14808-60-7 Quartz (SiO₂)

BOELV	Long-term value: 0.1* mg/m ³ *respirable fraction
-------	---

· **Additional information:** The lists valid during the making were used as basis.

· 8.2 Exposure controls

· Appropriate engineering controls No further data; see item 7.

· Individual protection measures, such as personal protective equipment

· General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Hand protection



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 6)

EU

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 03.07.2024

Version number 54 (replaces version 53)

Revision: 03.07.2024

Trade name: STEELKOTE EP AC+
· Penetration time of glove material

(Contd. of page 5)

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection


Tightly sealed goggles

* SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties
· General Information

Fluid

· Physical state

According to product specification

· Colour:

Characteristic

· Odour:

Not determined.

· Odour threshold:

Undetermined.

· Melting point/freezing point:

137-143 °C (CAS: 1330-20-7 xylene)

**· Boiling point or initial boiling point and
boiling range**

Flammable.

· Flammability

Not determined.

· Lower and upper explosion limit

Not determined.

· Lower:

Not determined.

· Upper:

35 °C

· Flash point:

500 °C (CAS: 1330-20-7 xylene)

· Ignition temperature:

Not determined.

· Decomposition temperature:

Mixture is non-polar/aprotic.

· pH

>60 s (ISO 6 mm)

· Viscosity:

Not determined.

· Kinematic viscosity at 20 °C

Not miscible or difficult to mix.

· Dynamic:

Not determined.

· Solubility

Not determined.

· water:

Not determined.

**· Partition coefficient n-octanol/water (log
value)**
13.5 hPa (CAS: 14808-60-7 Quartz (SiO₂))
· Vapour pressure at 1732 °C:
1.707 g/cm³
· Density and/or relative density

Not determined.

· Density at 20 °C:

Not determined.

· Relative density

Not determined.

· Vapour density

Not determined.

· 9.2 Other information

Liquid

· Appearance:

Product is not selfigniting.

· Form:

Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

**· Important information on protection of health
and environment, and on safety.**
· Auto-ignition temperature:

15.4 %

· Explosive properties:

(Contd. on page 7)

EU

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 03.07.2024

Version number 54 (replaces version 53)

Revision: 03.07.2024

Trade name: STEELKOTE EP AC+

(Contd. of page 6)

· VOC (EC)	14.87 %
· Solids content:	84.8 %
· Change in condition	
· Evaporation rate	Not determined.
Information with regard to physical hazard classes	
· Explosives	Void
· Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Flammable liquid and vapour.
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.
- **Skin corrosion/irritation** Causes skin irritation.
- **Serious eye damage/irritation** Causes serious eye irritation.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

(Contd. on page 8)

EU

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 03.07.2024

Version number 54 (replaces version 53)

Revision: 03.07.2024

Trade name: STEELKOTE EP AC+

(Contd. of page 7)

- **Additional toxicological information:**
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
Based on available date, the classification criteria are not met.
- **11.2 Information on other hazards**

- **Endocrine disrupting properties**

CAS: 68512-30-1	Phenol, methylstyrenated
-----------------	--------------------------

List II

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties**
For information on endocrine disrupting properties see section 11.
- **12.7 Other adverse effects**
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- **14.1 UN number or ID number**
 - **ADR/RID/ADN, ADN, IMDG**
 - **IATA**
 - **14.2 UN proper shipping name**
 - **ADR/RID/ADN, ADN, IMDG**
 - **IATA**
 - **14.3 Transport hazard class(es)**
 - **ADR/RID/ADN, IMDG**
 - **Class**
- | | |
|------|--------|
| Void | UN1263 |
| Void | PAINT |
| Void | |

(Contd. on page 9)

EU

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 03.07.2024

Version number 54 (replaces version 53)

Revision: 03.07.2024

Trade name: STEELKOTE EP AC+

(Contd. of page 8)

- **ADN**
- **ADN/R Class:** Void

IATA


- **Class** 3 Flammable liquids.
- **Label** 3
- **14.4 Packing group** Void
- **ADR/RID/ADN, IMDG** III
- **IATA** Not applicable.
- **14.5 Environmental hazards:** Not applicable.
- **14.6 Special precautions for user** Not applicable.
- **14.7 Maritime transport in bulk according to IMO instruments** Not applicable.
- **Transport/Additional information:**
- **ADR/RID/ADN** > 450 l: 3 F1, III
- **Remarks:**
- **IMDG** > 450 l: 3, III
- **Remarks:** Void
- **UN "Model Regulation":**

* SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**



GHS02 GHS07

Signal word Warning

Hazard-determining components of labelling:

phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2,2'-[((1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bis[oxirane]

Phenol, methylstyrenated

bis-[4-(2,3-epoxypropoxy)fenyl]propaan

oxirane, mono[(C12-14-alkyloxy)methyl] derivs

Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

(Contd. on page 10)

EU

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 03.07.2024

Version number 54 (replaces version 53)

Revision: 03.07.2024

Trade name: STEELKOTE EP AC+

(Contd. of page 9)

H317 May cause an allergic skin reaction.

Precautionary statements

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P241 Use explosion-proof [electrical/ventilating/lighting] equipment.
- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
- P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Directive 2012/18/EU

- **Named dangerous substances - ANNEX I** None of the ingredients is listed.

Seveso category P5c FLAMMABLE LIQUIDS

- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t

- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t

- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

REGULATION (EU) 2019/1148

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

This safety data sheet is in compliance with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

- **Department issuing SDS:** product safety department

(Contd. on page 11)

EU

Trade name: STEELKOTE EP AC+

(Contd. of page 10)

- **Date of previous version:** 23.05.2024
- **Version number of previous version:** 53

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

* Data compared to the previous version altered.

EU